


REVISION RECORD			
REV	DESCRIPTION	DFTM	DCR
RD3	Braid to 44 AWG	KP	
RD4	Filament Wrap & Braid Adjustment	KP, SB	



CONSTRUCTION

Signal Conductor: 0.0453" +/- 0.0002" (1.15 +/- 0.005mm), Silver Plated Copper per ASTM B-298
 Insulation: PFA, 0.0025" Wall Thickness, Blue
 Dual Monofilaments: PFA, Blue
 Setup: Dual Monofilaments twisted in a pair and helically wrapped around Signal Conductor
 Core Tube: FEP per applicable paragraph MIL-DTL-17, 0.120" +/- 0.002" (3.05 +/- 0.05mm) OD
 Inner Shield: Helically Overlapped Flat Silver Plated Copper per ASTM B-298
 Braid Shield: 44 AWG Silver Plated Copper per ASTM B-298, >85% Coverage
 Overall Shield Diameter: 0.138" +/- 0.002" (3.5 +/- 0.05mm)
 Jacket: FEP in accordance with MIL-DTL-17, Type IX
 Wall Thickness: 0.010" (0.25mm)
 Color: Blue

ELECTRICAL

Impedance: 50 +/- 1 ohms
 Propagation Delay: 1.19 +/- 0.01 ns/ft (3.90 ns/m)
 Velocity Of Propagation: 85%
 Capacitance: 23.8 pF/ft (77.0 pF/m)

GENERAL

Weight: 24.0 lbs/kft (35.4 kg/km)



U.S. Patent No. 6,812,401

This document is the property of TEMP-FLEX. It may not be disclosed, reproduced, or otherwise used without permission.	TEMP-FLEX CABLE, INC.		CAGE CODE: 0CGL7		
	26 Milford Road South Grafton, MA 01560 Phone: 508-839-5987 Fax: 508-839-4128			PART No: 141X-1701	
	DFTM: SB	DATE: 7/1/09	TITLE: Low Loss Microwave Coax, 17 AWG		
	APPD: KP	DATE: 7/1/09			SHEET 1 OF 1